



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			SEA			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED CLASS			
			REFLECTOR-PC			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC24V	15W	MAX. 0.766A	
			AC110V		MAX. 0.204A	
			AC220V		MAX. 0.102A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5		S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		SEA OUTLINE DRAWING			SEA		
	120~400	±0.2	±0.5	±1.2	±2.5		Qlight			SEA_OUT		
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4					DWG. NO.		
	0~10	±1°		±1°30'	±3°					SCALE	SIZE	REV
	10~50	±0°30'		±1°	±2°					N/S	A4	00
	50~120	±0°20'		±0°30'	±1°					SHEET		
	120~400	±0°10'		±0°13'	±0°30'					1/1		