



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SCDWS			
MATERIAL			HOUSING-PC+GF			
			LENS-PC			
			PROTECTION CAGE-SUS316L			
			-			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 2.933A	
			DC24V		MAX. 1.411A	
			AC110V		MAX. 0.360A	
			AC220V		MAX. 0.220A	
KIND OF SOUND			WS	5 Warning Sounds		
			WP	5 Special Warning Sounds		
			WM	5 Melodies		
			WA	5 Alarms		
			WV	5 Customizable Sounds		
VOLUME			MAX. 118dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2"PF			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1		TITLE SCDWS OUTLINE DRAWING		MODEL SCDWS			
	30~120	±0.15	±0.3	±0.8	±1.5					DWG. NO. SCDWS_OUT		
	120~400	±0.2	±0.5	±1.2	±2.5						SCALE N/S	SIZE A4
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							

Qlight

A4(297X210)