



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO	ELM-SOL
MATERIAL	HOUSING-PC
	LENS-PC
	REFLECTOR-HEAT RESISTING ABS
	SPEAKER COVER-SUS
	BOARD-AL
COLOR OF LENS	RED, BLUE
FLASHES PER MIN.	60~80
BATTERY VOLTAGE	12V
BATTERY CAPACITY	12Ah
OPERATING HOUR	96Hrs.
PROTECTION GRADE	WATER & DUST PROOF IP56
COLOR OF HOUSING	MAKER STANDARD
ACTION	LED LAMP FLASHING

L(LENGTH)	
ELM-1 (BLOCKS 2)	588mm
ELM-2 (BLOCKS 4)	868mm
ELM-3 (BLOCKS 6)	1148mm
ELM-4 (BLOCKS 8)	1428mm
ELM-5 (BLOCKS 10)	1708mm

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	c	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK		APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
	400~1000	±0.3	±0.8	±2	±4							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. ELM-SOL_OUT			
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	120~400	±0°10'		±0°13'	±0°30'							