


SIDE VIEW





TOP VIEW

※ POWER CABLE : Dura & Flex-F VU(0.5sq X 2C) 450mm

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QMHL-150-MF		
MATERIAL		BODY-AL		
		LENS-CHEMICAL TEMPERED GLASS		
		COVER-AL		
COLOR OF LENS		CLEAR		
USE VOLT.	LED	POWER CONSUMPTION	DC24V	CHIP LED
				12W
PROTECTION GRADE		WATER & DUST PROOF IP67 / IP69K		
CABLE ENTRY		M12		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-					
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE					
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20						
	3~6			±0.3	±0.5												
	6~30	±0.1	±0.2	±0.5	±1	TITLE QMHL-150-MF OUTLINE DRAWING											
	30~120	±0.15	±0.3	±0.8	±1.5							MODEL QMHL-150-MF					
	120~400	±0.2	±0.5	±1.2	±2.5												
400~1000	±0.3	±0.8	±2	±4	DWG. NO. QMHL-150-MF_OUT												
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'							±3°						
	10~50	±0°30'		±1°							±2°						
	50~120	±0°20'		±0°30'							±1°						
	120~400	±0°10'		±0°13'	±0°30'												
						SCALE N/S		SIZE A4	REV 00	SHEET 1/1							

A4(297X210)