



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO		SN-1		
MATERIAL		HOUSING-STEEL		
		BRACKET-STEEL		
USE VOLT.	CURRENT	DC12V	0.170A	
		DC24V	0.220A	
VOLUME				
MAX. 100dB				
PROTECTION GRADE				
WATER & DUST PROOF IP55				
CABLE ENTRY		ø10 LEAD HOLE		
COLOR OF HOUSING		RED		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	3~6			±0.3	±0.5			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	6~30	±0.1	±0.2	±0.5	±1			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	30~120	±0.15	±0.3	±0.8	±1.5			TITLE			MODEL		
	120~400	±0.2	±0.5	±1.2	±2.5			SN-1			SN-1		
	400~1000	±0.3	±0.8	±2	±4			OUTLINE DRAWING			SN-1_OUT		
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°			Qlight			DWG. NO.		
	10~50	±0°30'		±1°	±2°						SN-1_OUT		
	50~120	±0°20'		±0°30'	±1°			SCALE			N/S		
	120~400	±0°10'		±0°13'	±0°30'						SIZE		
												REV	SHEET
												00	1/1