



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO			SEAL-TI			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED CLASS			
			REFLECTOR-HEAT RESISTANT ABS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC24V	0.08W	0.140A	
			AC110V		0.110A	
			AC220V		0.070A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			LED STEADY/ FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5		K.H.PARK	J.K.HAN		J.I.BAE	3	2023. 5. 3.
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		SEAL-TI OUTLINE DRAWING			SEAL-TI		
	120~400	±0.2	±0.5	±1.2	±2.5					SEAL-TI_OUT		
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4					DWG. NO.		
	0~10	±1°		±1°30'	±3°					SCALE	SIZE	REV
	10~50	±0°30'		±1°	±2°					N/S	A4	00
	50~120	±0°20'		±0°30'	±1°							SHEET
	120~400	±0°10'		±0°13'	±0°30'							1/1