



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		STND100LR-N	
MATERIAL		HOUSING-ABS	
		LENS-AS	
		-	
COLOR OF LENS		RED(    ), AMBER(    ), GREEN(    ), BLUE(    )	
FLASHES. PER MIN		60 ~ 80	
USE VOLT.	CURRNET	DC12V	0.440A
		DC24V	0.340A
		AC110V AC220V	MAX. 0.150A
VOLUME		MAX. 105dB at 1m	
PROTECTION GRADE		WATER & DUST PROOF IP54	
CABLE ENTRY		ø10 LEAD HOLE	
COLOR OF HOUSING		MAKER STANDARD	
ACTION		LED STEADY / FLASHING LIGHT	

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW
	3~6			±0.3	±0.5			H.M.SEO	J.Y.KIM		J.W.KIM	DATE
	6~30	±0.1	±0.2	±0.5	±1							3
	30~120	±0.15	±0.3	±0.8	±1.5							2022.12.23
	120~400	±0.2	±0.5	±1.2	±2.5							
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			TITLE			MODEL	
	0~10	±1°	±1°30'	±3°				STND100LR-N			STND100LR-N	
	10~50	±0°30'	±1°	±2°				OUTLINE DRAWING			DWG. NO.	
	50~120	±0°20'	±0°30'	±1°				Qlight			STND100LR-N_OUT	
	120~400	±0°10'	±0°13'	±0°30'							SCALE	SHEET
								N/S	A4	REV	00	1/1

A4(297X210)