



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			STND125LR			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			-			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
REV. PER MIN			120 ~ 140			
USE VOLT.	POWER LED	CURRNET	DC12V	1W	0.630A	
			DC24V		0.540A	
			AC110V		MAX. 0.210A	
			AC220V			
VOLUME			MAX. 105dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			POWER LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	DATE
	6~30	±0.1	±0.2	±0.5	±1							3
	30~120	±0.15	±0.3	±0.8	±1.5							2019.03.20
	120~400	±0.2	±0.5	±1.2	±2.5							
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			TITLE			MODEL	
	0~10	±1°	±1°30'	±3°				STND125LR			STND125LR	
	10~50	±0°30'	±1°	±2°				OUTLINE DRAWING			DWG. NO.	
	50~120	±0°20'	±0°30'	±1°				Qlight			STND125LR_OUT	
	120~400	±0°10'	±0°13'	±0°30'							SCALE	SHEET
								N/S	A4	REV 00	1/1	