



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			STND100R			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			-			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES. PER MIN			120 ~ 140			
USE VOLT.	BULB	CURRNET	DC12V	10W	1.130A	
			DC24V		0.865A	
			AC110V		MAX. 0.350A	
			AC220V			
VOLUME			MAX. 105dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20	
	6~30	±0.1	±0.2	±0.5	±1	TITLE			MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5	STND100R OUTLINE DRAWING			STND100R			
	120~400	±0.2	±0.5	±1.2	±2.5				DWG. NO.			
	400~1000	±0.3	±0.8	±2	±4				STND100R_OUT			
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	SCALE		SIZE	REV	SHEET		
	10~50	±0°30'		±1°	±2°	N/S		A4	00	1/1		
	50~120	±0°20'		±0°30'	±1°							
	120~400	±0°10'		±0°13'	±0°30'							

Qlight

A4(297X210)