


MARK	DATE	REVISION	REVISER	APP. BY
△				
△				
△				

MODEL NO		SEAS		
MATERIAL		HOUSING-AL		
COLOR OF LENS		LENS-TEMPERED CLASS		
FLASHING PER MIN		RED( ), AMBER( ), GREEN( ), BLUE( )		
PROTECTION GRADE		60 ~ 80		
USE VOLT.	XENON CURRENT	6W	0.615A	
			0.105A	
			0.105A	
CABLE ENTRY		1/2" NPT		
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2		
ACTION		WATER & DUST PROOF IP66		
		XENON LAMP STROBE LIGHT		

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	Ⓞ	v	SURFACE FINISH
0.5~3	±0.05	±0.1	±0.2	-	
3~6			±0.3	±0.5	
6~30	±0.1	±0.2	±0.5	±1	
30~120	±0.15	±0.3	±0.8	±1.5	
120~400	±0.2	±0.5	±1.2	±2.5	
400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°			
	10~50	±0°30'	±1°30'		
	50~120	±0°20'	±1°	±2°	
	120~400	±0°10'	±0°30'	±1°	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	1	
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK	J.K.HAN	J.K.HAN	3	2019.03.20
TITLE <b>SEAS OUTLINE DRAWING</b>			MODEL <b>SEAS</b>		
			DWG. NO. <b>SEAS_OUT</b>		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		

A4(297X210)