


1 2 3 4 5 6

A
B
C
D

MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				



MODEL NO	QST50M-Ex	
MATERIAL	LENS-PC	
	FILTER LENS-PC	
	HOUSING-AL	
	COVER-AL	
COLOR OF LENS	RED(O), AMBER(O), GREEN(O), BLUE(O), WHITE(O)	
USE VOLTAGE	DC24V	
	AC110V~AC230V	
POWER CONSUMPTION	DC24V	7.2W
	AC110V~AC230V	22W
CURRENT (1LAYER)	DC24V	0.075A
	AC110V~AC230V	Max. 0.05A
CURRENT (BUZZER)	DC24V	0.05A
	AC110V~AC230V	Max. 0.04A
PROTECTION GRADE	WATER & DUST PROOF IP66	
CABLE ENTRY	CABLE ENTRY M12 or M16xP1.5	
COLOR OF HOUSING	MAKER STANDARD	
ACTION	LED STEADY / FLASHING LIGHT	

※ POWER CABLE
 AC : UL2464-22AWG-12C-700mm
 DC : UL2464-22AWG-10C-700mm

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	⊙	v	
0.5~3	±0.05	±0.1	±0.2	-	
3~6			±0.3	±0.5	
6~30	±0.1	±0.2	±0.5	±1	
30~120	±0.15	±0.3	±0.8	±1.5	
120~400	±0.2	±0.5	±1.2	±2.5	
400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°	
	10~50	±0°30'	±1°	±2°	
	50~120	±0°20'	±0°30'	±1°	
	120~400	±0°10'	±0°13'	±0°30'	

SURFACE FINISH		-							
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE			
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE				
J.Y.KIM	J.I.BAE		J.K.HAN	3	2026.04.24				
TITLE			QST50M-Ex OUTLINE DRAWING		MODEL QST50M-Ex				
DWG. NO.			QST50M-Ex_OUT						
SCALE	SIZE	REV	SHEET						
N/S	A4	00	1/1						

