



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S150ULR-FT			
MATERIAL			HOUSING-ABS			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	POWER LED	CURRENT	DC12V	3W	MAX. 0.422A	
			DC24V		MAX. 0.266A	
			AC110V		MAX. 0.082A	
			AC220V		MAX. 0.041A	
VOLUME			MAX. 90dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP44			
CABLE ENTRY			ø10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			POWER LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30	
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1								
	30~120	±0.15	±0.3	±0.8	±1.5								
	120~400	±0.2	±0.5	±1.2	±2.5								
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.		S150ULR-FT_OUT		
	10~50	±0°30'		±1°	±2°				SCALE		SIZE	REV	SHEET
	50~120	±0°20'		±0°30'	±1°				N/S	A4	00	1/1	
	120~400	±0°10'		±0°13'	±0°30'								

Qlight

A4(297X210)