



MODEL NO		QCML-SERIES-7C							
MATERIAL		SIDE COVER-PC							
		LENS-PC							
		HEAT SINK-AL							
		BRACKET-PC							
MODEL		QCML-200-7C	QCML-300-7C	QCML-400-7C	QCML-500-7C	QCML-600-7C	QCML-900-7C	QCML-1200-7C	QCML-1500-7C
POWER CONSUMPTION	DC24V	4.7W	5.6W	9.4W	10.3W	11.4W	17W	22.2W	28W
LED		CHIP LED							
PROTECTION GRADE		WATER & DUST PROOF IP67/IP69K							

MODEL	A	B	C	D
QCML-200-7C	262	228	45~217	2
QCML-300-7C	362	328	45~317	2
QCML-400-7C	462	428	45~417	2
QCML-500-7C	562	528	45~517	2
QCML-600-7C	662	628	45~617	2
QCML-900-7C	962	928	45~917	3
QCML-1200-7C	1262	1228	45~1217	4
QCML-1500-7C	1562	1528	45~1517	4

※ D : Recommended quantity of mounting brackets

※ POWER CABLE : DC TYPE - UL2464-AWG22(0.3sqx4C) 450mm

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-		-		-		1		-			
FOR LINEAR DIMENSIONS		f	m	c	Ⓥ		Nr.	DWG. NO.	TITLE/ NAME			MAT'L		QTY	REFERENCE			
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY			APRV BY	VIEW	DATE				
	3~6			±0.3	±0.5		C.S.GWAK	J.H.PARK				J.K.HAN	3	2021.07.27				
	6~30	±0.1	±0.2	±0.5	±1		TITLE QCML-SERIES-7C OUTLINE DRAWING								MODEL QCML-SERIES-7C			
	30~120	±0.15	±0.3	±0.8	±1.5										QCML-SERIES-7C			
	120~400	±0.2	±0.5	±1.2	±2.5										QCML-SERIES-7C			
400~1000	±0.3	±0.8	±2	±4	QCML-SERIES-7C													
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°							DWG. NO. QCML-SERIES-7C						
	10~50	±0°30'		±1°	±2°							SCALE 1/1				SIZE A4	REV 00	SHEET 1/1
	50~120	±0°20'		±0°30'	±1°													
	120~400	±0°10'		±0°13'	±0°30'													