



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			S60ADB			
MATERIAL			HOUSING-ABS			
			LENS-AS			
			REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	BULB	CURRENT	DC12V	10W	MAX. 1.008A	
			DC24V		MAX. 0.556A	
			AC110V		MAX. 0.127A	
			AC220V		MAX. 0.064A	
VOLUME			MAX. 100dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			10 X 10			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			BULB STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.3	±0.5
	30~120	±0.15	±0.3	±0.5	±1
	120~400	±0.2	±0.5	±0.8	±1.5
	400~1000	±0.3	±0.8	±1.2	±2.5
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±2°	±4°
	10~50	±0°30'	±1°	±1°30'	±3°
	50~120	±0°20'	±1°	±1°	±2°
	120~400	±0°10'	±0°30'	±1°	±1°
		±0°10'	±0°13'	±0°30'	±0°30'

SURFACE FINISH		-		1	
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
S60ADB OUTLINE DRAWING			S60ADB		
			DWG. NO.		
			S60ADB_OUT		
SCALE		SIZE	REV	SHEET	
N/S		A4	00	1/1	