



MARK	DATE	REVISION	REVISER	APP. BY
▲				
▲				
▲				

MODEL NO		SEHN25		
MATERIAL		HOUSING-STEEL		
		HORN HOUSING-STEEL		
USE VOLT.	CURRENT	DC12V	MAX. 2.211A	
		DC24V	MAX. 1.022A	
		AC110V	MAX. 0.226A	
		AC220V	MAX. 0.113A	
KIND OF SOUND	WS	5 Warning Sounds		
	WM	5 Melodies		
	WA	5 Alarms		
	WV	5 Customizable sounds		
VOLUME		MAX. 115dB		
PROTECTION GRADE		WATER & DUST PROOF IP55		
CABLE ENTRY		ø21 LEAD HOLE		
COLOR OF HOUSING		RED		

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓞ	v		
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	1	-
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
SEHN25 OUTLINE DRAWING			SEHN25		
			DWG. NO.		
			SEHN25_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		