



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			SCDWL			
MATERIAL			HOUSING-PC+GF			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	-	MAX. 2.633A	
			DC24V		MAX. 1.288A	
			AC110V		MAX. 0.308A	
			AC220V		MAX. 0.154A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2"PF			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY/ FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-	
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30	
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1		TITLE SCDWL OUTLINE DRAWING		MODEL SCDWL				
	30~120	±0.15	±0.3	±0.8	±1.5					DWG. NO. SCDWL_OUT			
	120~400	±0.2	±0.5	±1.2	±2.5						SCALE N/S	SIZE A4	REV 00
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								

A4(297X210)