

Dual-Facing Electronic Sounders for Vessels and Heavy Industry Applications

SHDN30



PRODUCT SPECIFICATION

SHDN30

Materials Housing-Al, Horn housing-PC

Ambient operating temperature -30°C to +50°C

Protection rating IP56

Cable entry 1/2" PF

Standard Housing color MUNSELL No. 7.5BG 7/2

Can adjust sound volume with the switch built inside the unit



SHDN30
(Max.114dB x 2)

- Alarm horns with tightly sealed structure has excellent durability. Suitable for vessels, steel industry, and outdoor plant applications
- Alarm horns with tightly sealed structure has excellent durability. Suitable for vessels, steel industry, and outdoor plant applications
- Aluminum housing provides excellent durability
- A variety of sound selection between warning sounds, alarm sounds, melodies and voice messages to fit your sophisticated application needs
- Terminals located inside the terminal box or product

SHDN30 Electronic Sounders, Max.114dBx2 Direct Mount Type

Model number	Voltage	Current	Sound pattern and volume	Certificates	Weight
SHDN30	DC12V	3A	·WS-5 Warning sounds: Max.114dBx2	-	3.49kg
	DC24V	2.15A	·WP-5 Special warning sounds: Max.114dBx2		
	AC110V	500mA	·WM-5 Melodies: Max.110dBx2		4.21kg
	AC220V	240mA	·WA-5 Alarms: Max.114dBx2 ·WV-5 Customizable voices: 108-113dBx2		


※ Please refer to [Sound tone and combination for standard product] on this catalogue for detailed sound tone specification.

※ Max.built-in volume feature is based on WS, WP-Ch1 / WM-Ch4 / WA-Ch4.

※ In case of customized WV 5 tone type, there may be difference of volume depending on user's audio file type.

Sound Selection Instructions


- Standard Type: Select sound using the switch inside of the unit. When you turn on the dip switch for each channel, the designated sound will be played. designated sound will be played.



- Customized type : Select using the external contact(LC)
You can select the audible sound pattern using external contacts or transistor with a customized external sound line(Model number : -LC).
- Product can be wired regardless of polarity.


Technical Diagram

Units: mm




Wiring Instructions

SHDN30-DC/AC



External Transistor-NPN



Customization

- 3/4" PF Cable entry
- Customized external sound line type available

Ordering Specification

SHDN30	-	WP	-	110	-	LC
[Model number]		[Sound]		[Voltage]		[Sound selection]
SHDN30		WS-Warning sounds WP-Special warning sounds WM-Melodies WA-Alarms WV-Customizable voices		12-DC12V 24-DC24V 110-AC110V 220-AC220V		None-Built-in switch LC-External contact