






MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO		QWH50-TI	
MATERIAL		HORN-PC	
		HOUSING-PC+ABS	
		-	
USE VOLT.	CURRENT	DC12V ~ 24V	MAX. 3.520A
		AC110V ~ 220V	MAX. 0.480A
CHANNEL		BINARY INPUT	31CH
KIND OF SOUND	VOLUME	WARNING SOUNDS 31Ch	MAX. 123dB at 1m
PROTECTION GRADE		WATER & DUST PROOF - IP66	
CABLE ENTRY		CABLE GLAND "PG13.5" x 2	
COLOR OF HOUSING		MAKER STANDARD	



FITTING HOLES

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-						
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QTY
	3~6	±0.05	±0.1	±0.2	-	DSND BY		CHKD BY		CHKD BY	APRV BY	VIEW	DATE
	6~30	±0.1	±0.2	±0.5	±1	C.S.GWAK		J.H.PARK			J.K.HAN	3	2021.10.08
	30~120	±0.15	±0.3	±0.8	±1.5	TITLE QWH50-TI OUTLINE DRAWING							
	120~400	±0.2	±0.5	±1.2	±2.5								
	400~1000	±0.3	±0.8	±2	±4	MODEL QWH50-TI							
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								
								DWG. NO.		QWH50-TI_OUT			
								SCALE	SIZE	REV	SHEET		
								1/1	A4	00	1/1		