



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			SSL400M			
MATERIAL			HOUSING-AL			
			LENS-PC			
COLOR OF LENS			RED, AMBER, GREEN, BLUE			
USE VOLT.	LED	CURRENT	DC24V	0.08W	0.604A	
			AC110V		0.160A	
			AC220V		0.160A	
PROTECTION GRADE			WATER & DUST PROOF IP68			
CONNECTOR			M12-5PIN or C10 CABLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	3~6			±0.3	±0.5			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	6~30	±0.1	±0.2	±0.5	±1			C.S.GWAK	J.H.PARK		J.K.HAN	3	2021.08.30
	30~120	±0.15	±0.3	±0.8	±1.5			TITLE			MODEL		
	120~400	±0.2	±0.5	±1.2	±2.5			SSL400M			SSL400M		
	400~1000	±0.3	±0.8	±2	±4			OUTLINE DRAWING			SSL400M_OUT		
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°				Qlight			DWG. NO.		
	10~50	±0°30'	±1°	±2°							SCALE		
	50~120	±0°20'	±0°30'	±1°							1/1	A4	01
	120~400	±0°10'	±0°13'	±0°30'							1/1	1/1	1/1