



S180U

PRODUCT SPECIFICATION

S180U

Materials Lens-AS, Housing-ABS, Reflector-PC

Ambient operating temperature -20°C to +50°C

Volume Max.90dB at 1m

Protection rating IP44

Revolving speed 120-140RPM

- Excellent long distance signal transmission effect with 35W capacity bulb and dual reflectors
- A spare bulb is provided inside the product for quick replacement if provided

S180U Bulb Revolving Warning Light

Model number	Voltage	Current	Bulb			Certificates	Weight	Color
			Spec	Standard	Parts no			
S180U	DC12V	3.4A	12V35W	RP35 15S	29	CE	0.89kg	● R-Red
	DC24V	1.65A	24V35W	RP35 15S	30		0.89kg	● A-Amber
	AC110V	410mA	12V35W	RP35 15S	29		1.65kg	● G-Green
	AC220V	190mA	12V35W	RP35 15S	29		1.65kg	● B-Blue

※ CE compliant: DC24V


Technical Diagram

Units: mm




S180U has a spare bulb inside the product for easy replacement if required.

S180U



※ Products that Mount size 120mm are available upon request



Wiring Instructions

- External Power line - UL1015 AWG18(0.75sq) x 2C 400mm
- DC Type: Black output line is negative(-)
- For the wiring of 110 & 220VAC combination model, 110VAC model is connected to black and white wires while 220VAC model is connected to black and red wires.

Customization

- 2 buzzer sound types: Both prolonged (beep, beep) and staccato(beep, beep, beep) buzzer output available
- The product mount hole size 120mm (PCD 120mm)

Ordering Specification

S180U	-	BZ	-	220	-	R
[Model number]		[Buzzer option]		[Voltage]		[Color]
S180U		(None)		12-DC12V		● R-Red
		- No buzzer		24-DC24V		● A-Amber
		BZ		110-AC110V		● G-Green
		- Built-in buzzer		220-AC220V		● B-Blue