



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL NO	SL120N4-KE -CRB(PC)	SL120N4-KE -CRB(PF)	SL120N4-KE -CRB(PW)
MATERIAL	ALDC 12.1 + POLY CARBONATE + Etc.		
POWER CONSUMPTION	120W		
COLOR OF LENS	CLEAR	FROSTED	CLEAR
TOTAL LUMEN	18,000(lm)	16,200(lm)	17,400(lm)
BEAM ANGLE	110°	100°	60°
LUMINOUS EFFICACY	150(lm/W)	135(lm/W)	145(lm/W)
COLOR TEMPERATURE	5700K		
INPUT VOLTAGE	AC 220V		
PROTECTION GRADE	WATER & DUST PROOF IP65		
CABLE ENTRY	M10		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-			-		1		-	
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE			
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY Y.C.KO	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2017.11.22				
	3~6			±0.3	±0.5										
	6~30	±0.1	±0.2	±0.5	±1	TITLE LED 고현장등 OUTLINE DRAWING		DWG. NO. SL120N4-KE-CRB(PF)_OUT	SCALE N/S	SIZE A4	REV 00	SHEET 1/1			
	30~120	±0.15	±0.3	±0.8	±1.5										
	120~400	±0.2	±0.5	±1.2	±2.5										
400~1000	±0.3	±0.8	±2	±4											
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°										
	10~50	±0°30'		±1°	±2°										
	50~120	±0°20'		±0°30'	±1°										
	120~400	±0°10'		±0°13'	±0°30'										