

Panel mounted Speaker for Multi-channel

CPK-10



PRODUCT SPECIFICATION

CPK-10

Materials ABS
Ambient operating temperature -25°C to +50°C
Protection rating IP65
Volume Max.90dB at 1m
Compliant with RoHS directive

- Panel type signal phone that outputs clear and cheerful 8-48Khz MP3 Audio chords using IO input
- Compatible with NPN and PNP depending on the connection method by using the terminal block for connection on the back of the product
- Plays 255ea of MP3 files with binary input method
- Save MP3 sound source using USB C-TYPE cable



CPK-10

CPK-10 Signal phone for multi-channel, Max.90dB

Model number	Sound type	Volume	Voltage	Current	Certificates	Weight
CPK-10	MP3 File (255 Sounds)	Max.90dB	DC12V-24V	Max. 600mA	CE	0.21kg

※ DC type model has a free-voltage range of 10V-36V


※ When playing MP3 files, there may be difference of volume depending on user's audio file type.



Terminal box for wiring of power and IO communication cable(back side)


Technical Diagram

Units: mm




Wiring Instructions

-CPK-10 "-"External Contact




-CPK-10 "+"External Contact




-External transistor

NPN-TRANSISTOR



PNP-TRANSISTOR



Ordering Specification

