



MARK	DATE	REVISION	REVISER	APP. BY
1				
2				
3				

MODEL NO			SESA-TI			
MATERIAL			HOUSING-AL			
			LENS-TEMPERED CLASS			
			REFLECTOR-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC24V	15W	1.640A	
			AC110V		0.320A	
			AC220V		0.200A	
VOLUME			MAX. 118dB			
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" NPT			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.3	±0.5
	30~120	±0.15	±0.3	±0.5	±1
	120~400	±0.2	±0.5	±0.8	±1.5
	400~1000	±0.3	±0.8	±1.2	±2.5
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±2°	±3°
	10~50	±0°30'	±1°	±1°	±2°
	50~120	±0°20'	±0°30'	±1°	±1°
	120~400	±0°10'	±0°13'	±0°30'	±0°30'

SURFACE FINISH		-	-	-	-	1	-
		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
		K.H.PARK	J.K.HAN	J.I.BAE	J.I.BAE	3	2023. 5. 3.
		TITLE			MODEL		
		SESA-TI OUTLINE DRAWING			SESA-TI		
					SESA-TI_OUT		
					SCALE	SIZE	REV
					N/S	A4	00
					SHEET		
					1/1		

