



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			S125S			
MATERIAL			HOUSING-ABS			
			LENS-AS			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.			60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V ~ DC24V	6W	MAX. 1.000A	
			AC110V		0.135A	
			AC220V		0.105A	
PROTECTION GRADE			WATER & DUST PROOF IP54			
CABLE ENTRY			φ10 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.			
	10~50	±0°30'		±1°	±2°				S125S_OUT			
	50~120	±0°20'		±0°30'	±1°				SCALE			
	120~400	±0°10'		±0°13'	±0°30'				N/S			
									SIZE			
						A4						
						REV						
						00						
						SHEET						
						1/1						

A4(297X210)