


MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		S150US			
MATERIAL		HOUSING-ABS			
		LENS-PC			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.		60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V ~ DC24V	6W	MAX. 1.000A
			AC110V		0.135A
			AC220V		0.105A
VOLUME		MAX. 90dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP44			
CABLE ENTRY		φ10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		XENON LAMP STROBE LIGHT			

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	(C)	v		
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2019.03.20
TITLE			MODEL		
S150US OUTLINE DRAWING			S150US		
			DWG. NO.		
			S150US_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		