



MARK	DATE	REVISION	REVISER	APP.BY
①				J.K.HAN
②				
③				

MODEL NO	PSSH6560S-AL-HJ
MATERIAL	HEAD & BODY - DIE CAST BRASS BOLT,NUT,ROLLER,LEVER - SUS
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP56
CABLE ENTRY	PF 3/4"
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC

Operating Characteristics

OF max.g	1,680
RF min.g	280
PT	25±5°
MD max.	10°
TT min.	70°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH							
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY J.H.PARK	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.06.19		
	3~6			±0.3	±0.5								
	6~30	±0.1	±0.2	±0.5	±1	TITLE PSSH6560S-AL-HJ OUTLINE DRWAING		DWG. NO. PSSH6560S-AL-HJ-OUT					
	30~120	±0.15	±0.3	±0.8	±1.5				SCALE N/S	SIZE A4	REV 00	SHEET 1/1	
	120~400	±0.2	±0.5	±1.2	±2.5								
400~1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°								
	10~50	±0°30'		±1°	±2°								
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								