



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL No.	SLP2130-SW
MATERIAL	HEAD & BODY - DIE CAST AL BOLT,NUT & ETC. - SUS304
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP66
CABLE ENTRY	PF 1/2"
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC

■ Operating Characteristics	
OF max.g	150
PT	20mm ± 10mm
360° without direction	

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-						
FOR LINEAR DIMENSIONS		f	m	c	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	MODEL	VIEW	DATE	
	3~6			±0.3	±0.5		U.H.LEE	U.H.LEE		J.K.HAN	3	2023.04.05	
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5		SLP2130-SW OUTLINE DRAWING			SLP2130-SW			
	120~400	±0.2	±0.5	±1.2	±2.5					DWG. NO.			
400~1000	±0.3	±0.8	±2	±4	SLP2130-SW-OUT								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	SCALE		SIZE	REV	SHEET			
	10~50	±0°30'		±1°	±2°	1/1		A4	02	1/1			
	50~120	±0°20'		±0°30'	±1°								
	120~400	±0°10'		±0°13'	±0°30'								