


MODEL No.	SW2TS-AL
MATERIAL	HEAD & BODY - DIE CAST BRASS BOLT, NUT, ROLLER & ETC. - SUS304
CONTACT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP66
CABLE ENTRY	PF 1/2
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100M $\Omega$ MIN. at 500V DC

■ Operating Characteristics

OF max.g	1,380
RF min.g	260
PT	15° $\pm$ 5°
MD max.	5°
TT min	60°

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH					
FOR LINEAR DIMENSIONS		f	g	h		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y
	0.5~3	$\pm 0.05$	$\pm 0.1$	$\pm 0.2$	—	DSND BY	U.H LEE	CHKD BY	U.H LEE	APRV BY
FOR LINEAR DIMENSIONS	3~6	$\pm 0.1$	$\pm 0.2$	$\pm 0.3$	$\pm 0.5$	VIEW	3	DATE	2012.01.27	REFERENCE
	6~30	$\pm 0.15$	$\pm 0.3$	$\pm 0.5$	$\pm 1$	OUT-LINE DRAWING (SW2TS-AL)				
	30~120	$\pm 0.2$	$\pm 0.5$	$\pm 1.2$	$\pm 2.5$	MODEL SW2TS-AL				
	120~400	$\pm 0.3$	$\pm 0.8$	$\pm 2$	$\pm 4$	DWG. NO. SW2TS-AL-OUT				
	400~1000	$\pm 0.5$	$\pm 1.2$	$\pm 2$	$\pm 4$	SCALE 1/1 SIZE A3 REV 00 SHEET 1/1				
FOR ANGULAR DIMENSIONS	0~10	$\pm 1^\circ$	$\pm 1'30''$	$\pm 3'$						
	10~50	$\pm 0'30''$	$\pm 1'$	$\pm 2'$						
	50~120	$\pm 0'20''$	$\pm 0'30''$	$\pm 1'$						
	120~400	$\pm 0'10''$	$\pm 0'13''$	$\pm 0'30''$						