

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				


MODEL NO	SH6560S-FL
MATERIAL	HEAD & BODY - DIE CAST BRASS BOLT,NUT,ROLLER,LEVER - SUS
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP56
CABLE ENTRY	PF 3/4"
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC

■ Operating Characteristics

OF max.g	1,420
PT	30°
OT	55°

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f ±0.05	m ±0.1	Ⓢ ±0.2	v -
	3~6			±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
	400~1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	
	10~50	±0°30'		±1°	
	50~120	±0°20'		±0°30'	
	120~400	±0°10'		±0°13'	

SURFACE
FINISH

-							
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE	
DSND BY J.H.PARK	CHKD BY J.H.PARK	CHKD BY	APRV BY J.K.HAN	VIEW 3	DATE 2020.11.20		
TITLE SH6560S-FL OUTLINE DRWAING				MODEL SH6560S-FL			
				DWG. NO. SH6560S-FL-OUT			
				SCALE N/S	SIZE A4	REV 00	SHEET 1/1