




| MARK | DATE | REVISION | REVISER | APP.BY |
|------|------|----------|---------|--------|
| 1 | | | | |
| 2 | | | | |
| 3 | | | | |

| | |
|-----------------------|---|
| MODEL NO | SH6560S-LRL |
| MATERIAL | HEAD & BODY - DIE CAST BRASS BOLT,NUT,ROLLER,LEVER - SUS |
| CONATCT | 2CKT-DB, 1A1B, 250VAC 6A |
| PROTECTION GRADE | WATER & DUST PROOF - IP56 |
| CABLE ENTRY | PF 3/4" |
| COLOR | MAKER STANDARD |
| INSULATION RESISTANCE | 100MΩ MIN. at 500V DC |

Operating Characteristics

| | |
|----------|-------|
| OF max.g | 1,300 |
| RF min.g | 210 |
| PT | 25±5° |
| MD max. | 10° |
| TT min. | 70° |

| ISO2768-1 : CLASS OF TOLERANCE | | | | | | SURFACE FINISH | - | | | | | | | |
|--------------------------------|---------|--------|------|--------|-----------------|---|----------|---|-------------|------|------------|-------|------|-----------|
| FOR LINEAR DIMENSIONS | | f | m | Ⓒ | v | | Nr. | DWG. NO. | TITLE/ NAME | | | MAT'L | QT'Y | REFERENCE |
| | 0.5~3 | ±0.05 | ±0.1 | ±0.2 | - | DSND BY | CHKD BY | CHKD BY | APRV BY | VIEW | DATE | | | |
| | 3~6 | | | ±0.3 | ±0.5 | J.H.PARK | J.H.PARK |  | J.K.HAN | 3 | 2020.11.20 | | | |
| | 6~30 | ±0.1 | ±0.2 | ±0.5 | ±1 | TITLE | | | MODEL | | | | | |
| | 30~120 | ±0.15 | ±0.3 | ±0.8 | ±1.5 | SH6560S-LRL OUTLINE DRWAING | | | SH6560S-LRL | | | | | |
| | 120~400 | ±0.2 | ±0.5 | ±1.2 | ±2.5 |  | | | DWG. NO. | | | | | |
| 400~1000 | ±0.3 | ±0.8 | ±2 | ±4 | SH6560S-LRL-OUT | | | | | | | | | |
| FOR ANGULAR DIMENSIONS | 0~10 | ±1° | | ±1°30' | ±3° |  | | | SCALE | SIZE | REV | SHEET | | |
| | 10~50 | ±0°30' | | ±1° | ±2° | | | | N/S | A4 | 00 | 1/1 | | |
| | 50~120 | ±0°20' | | ±0°30' | ±1° | | | | | | | | | |
| | 120~400 | ±0°10' | | ±0°13' | ±0°30' | | | | | | | | | |