



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO	SH6560S-W
MATERIAL	HEAD & BODY - DIE CAST BRASS BOLT,NUT,LEVER - SUS
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP56
CABLE ENTRY	PF 3/4"
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC

Operating Characteristics

OF max.g	1,800
RF min.g	1,400
PT	25°
MD max.	15°
TT min.	50°

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓢ	v
	3~6	±0.05	±0.1	±0.2	-
	6~30	±0.1	±0.2	±0.3	±0.5
	30~120	±0.15	±0.3	±0.5	±1
	120~400	±0.2	±0.5	±0.8	±1.5
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±1.2	±2.5
	0~10	±1°	±1°	±1°	±3°
	10~50	±0°30'	±1°	±1°	±2°
	50~120	±0°20'	±1°	±1°	±1°
	120~400	±0°10'	±1°	±1°	±1°

SURFACE FINISH	-								
	Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE		
	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE			
	J.H.PARK	J.H.PARK		J.K.HAN	3	2019.06.25			
	TITLE				MODEL				
	SH6560S-W OUTLINE DRWAING				SH6560S-W				
				DWG. NO.				SH6560S-W-OUT	
				SCALE	SIZE	REV	SHEET		
				N/S	A4	00		1/1	

Qlight