



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL No.	SLP5130-AL
MATERIAL	HEAD & BODY - DIE CAST AL BOLT,NUT & ETC. - SUS304 , ROLLER - POM
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	EXPLOSION PROOF - Ex d IIC T6 / Ex tb IIIC T85°C WATER & DUST PROOF - IP66
CABLE ENTRY	STANDARD - NPT 1/2 OPTION - NPT 3/4
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC
CERTIFICATE	KOSHA, ABS, IECEx, KIMM, ATEX

■ Operating Characteristics

OF max.g	1,300
RF min.g	210
PT	25° ± 5°
MD max.	10°
TT min	70°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-							
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY		CHKD BY	CHKD BY	MODEL	VIEW	DATE		
	3~6			±0.3	±0.5	S.H.KIM		J.H.PARK		J.K.HAN	3	2012.01.27		
	6~30	±0.1	±0.2	±0.5	±1									
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°									
	10~50	±0°30'		±1°	±2°									
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									
						TITLE SLP5130-AL OUTLINE DRAWING				MODEL SLP5130-AL				
										DWG. NO. SLP5130-AL-OUT				
										SCALE N/S		SIZE A4	REV 00	SHEET 1/1

Qlight