


MARK	DATE	REVISION	REVISER	APP .BY

MODEL No.	SLP5130-RL
MATERIAL	HEAD & BODY - DIE CAST AL BOLT,NUT & ETC. - SUS304 ,ROLLER - POM
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	EXPLOSION PROOF - Ex d II C T6 / Ex tb IIIC T85°C WATER & DUST PROOF - IP66
CABLE ENTRY	STANDARD - NPT 1/2 OPTION - NPT 3/4
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC
CERTIFICATE	ATEX

■ Operating Characteristics

OF max.g	1,300
RF min.g	210
PT	25° ± 5°
MD max.	10°
TT min	70°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH									
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME				MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY		CHKD BY	CHKD BY	MODEL	VIEW	DATE		
	3~6			±0.3	±0.5		S.H.KIM		J.H.PARK		J.K.HAN	3	2012.01.27		
	6~30	±0.1	±0.2	±0.5	±1		TITLE		SLP5130-RL		MODEL		SLP5130-RL		
	30~120	±0.15	±0.3	±0.8	±1.5				OUTLINE DRAWING						
	120~400	±0.2	±0.5	±1.2	±2.5										
400~1000	±0.3	±0.8	±2	±4											
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°						DWG. NO.		SLP5130-RL-OUT		
	10~50	±0°30'		±1°	±2°										
	50~120	±0°20'		±0°30'	±1°						SCALE		SIZE	REV	SHEET
	120~400	±0°10'		±0°13'	±0°30'						N/S		A4	00	1/1