


MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL No.	SLP5130-RP
MATERIAL	HEAD & BODY - DIE CAST AL BOLT,NUT,ROLLER & ETC. - SUS304
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	EXPLOSION PROOF - WATER & DUST PROOF - IP66
CABLE ENTRY	STANDARD - NPT 1/2 OPTION - NPT 3/4
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC
CERTIFICATE	-

■ Operating Characteristics

OF max.g	2,850
RF max.g	810
PT	2.0mm
MD max	1.0mm

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH										
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE				
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY		CHKD BY	CHKD BY	MODEL J.K.HAN	VIEW 3	DATE 2012.01.27			
	3~6			±0.3	±0.5		S.H.KIM		J.H.PARK							
	6~30	±0.1	±0.2	±0.5	±1											
	30~120	±0.15	±0.3	±0.8	±1.5											
	120~400	±0.2	±0.5	±1.2	±2.5											
400~1000	±0.3	±0.8	±2	±4	TITLE SLP5130-RP OUTLINE DRAWING			MODEL SLP5130-RP								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°					DWG. NO. SLP5130-RP-OUT						
	10~50	±0°30'		±1°	±2°											
	50~120	±0°20'		±0°30'	±1°											
	120~400	±0°10'		±0°13'	±0°30'											
										SCALE N/S				SIZE A4	REV 00	SHEET 1/1

A4(297X210)