



MARK	DATE	REVISION	REVISER	APP. BY
1				J.K.HAN
2				
3				

MODEL NO	SH8560-FL/ SH8560S-FL
MATERIAL	SH8560-FL: HEAD & BODY - DIE CAST AL SH8560S-FL: HEAD & BODY - DIE CAST BRASS
	BOLT,NUT,ROLLER,LEVER - SUS
CONATCT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP56
CABLE ENTRY	PF 3/4"
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100M $\Omega$ MIN. at 500V DC

#### Operating Characteristics

OF max.g	1,800
PT	30°
OT	55°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-								
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QTY	REFERENCE	
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY C.S.GWAK	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2021.08.27			
	3~6			±0.3	±0.5										
	6~30	±0.1	±0.2	±0.5	±1										
	30~120	±0.15	±0.3	±0.8	±1.5										
	120~400	±0.2	±0.5	±1.2	±2.5										
400~1000	±0.3	±0.8	±2	±4											
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. SH8560/ SH8560S-FL-OUT						
	10~50	±0°30'		±1°	±2°				SCALE 1/1				SIZE A4	REV 00	SHEET 1/1
	50~120	±0°20'		±0°30'	±1°										
	120~400	±0°10'		±0°13'	±0°30'										