




MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	SMJ-H8-FL
MATERIAL	HEAD & BODY - BRASS BOLT, NUT - SUS LEVER - NBR
CONTACT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF - IP56
CABLE ENTRY	PF 3/4"
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. at 500V DC

■ Operating Characteristics

OF max.g	1,800
PT	30°
OT	55°

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-						
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME			MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY		APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	J.K.HAN	J.H.PARK		J.I.BAE	3	2022.6.17		
	6~30	±0.1	±0.2	±0.5	±1	TITLE			SMJ-H8-FL				
	30~120	±0.15	±0.3	±0.8	±1.5	OUTLINE DRWAING			MODEL				
	120~400	±0.2	±0.5	±1.2	±2.5				SMJ-H8-FL				
400~1000	±0.3	±0.8	±2	±4	SMJ-H8-FL-OUT								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.				
	10~50	±0°30'		±1°	±2°				SMJ-H8-FL-OUT				
	50~120	±0°20'		±0°30'	±1°				SCALE				
	120~400	±0°10'		±0°13'	±0°30'				1/1				

Qlight