



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO		STND125LR-N	
MATERIAL		HOUSING-ABS	
		LENS-AS	
		-	
COLOR OF LENS		RED(    ), AMBER(    ), GREEN(    ), BLUE(    )	
FLASHES. PER MIN		60 ~ 80	
USE VOLT.	CURRNET	DC12V	0.645A
		DC24V	0.365A
		AC110V~AC220V	MAX. 0.200A
VOLUME		MAX. 105dB at 1m	
PROTECTION GRADE		WATER & DUST PROOF IP54	
CABLE ENTRY		ø10 LEAD HOLE	
COLOR OF HOUSING		MAKER STANDARD	
ACTION		LED STEADY / FLASHING LIGHT	

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY H.M.SEO	CHKD BY J.Y.KIM	CHKD BY 	APRV BY J.W.KIM	VIEW 3	DATE 2022.12.23
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.			
	10~50	±0°30'		±1°	±2°				STND125LR-N_OUT			
	50~120	±0°20'		±0°30'	±1°				SCALE			
	120~400	±0°10'		±0°13'	±0°30'				N/S	SIZE	REV	SHEET
										A4	00	1/1

A4(297X210)