



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		STND125R-N	
MATERIAL		HOUSING-ABS	
		LENS-AS	
		-	
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()	
FLASHES. PER MIN		60 ~ 80	
USE VOLT.	CURRNET	DC12V	1.180A
		DC24V	0.725A
		AC110V~AC220V	MAX. 0.355A
VOLUME		MAX. 105dB at 1m	
PROTECTION GRADE		WATER & DUST PROOF IP54	
CABLE ENTRY		φ10 LEAD HOLE	
COLOR OF HOUSING		MAKER STANDARD	
ACTION		LED STEADY / FLASHING LIGHT	

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-																	
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE																	
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY H.M.SEO	CHKD BY J.Y.KIM	CHKD BY 	APRV BY J.W.KIM	VIEW 3	DATE 2022.12.23																		
	3~6			±0.3	±0.5																								
	6~30	±0.1	±0.2	±0.5	±1	TITLE STND125R-N OUTLINE DRAWING																							
	30~120	±0.15	±0.3	±0.8	±1.5																								
	120~400	±0.2	±0.5	±1.2	±2.5																								
400~1000	±0.3	±0.8	±2	±4	MODEL STND125R-N																								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'							±3°																		
	10~50	±0°30'		±1°	±2°	DWG. NO. STND125R-N_OUT																							
	50~120	±0°20'		±0°30'	±1°													SCALE N/S											
	120~400	±0°10'		±0°13'	±0°30'																			SIZE A4					
	REV 00		SHEET 1/1																										

