



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			Q100LP			
MATERIAL			HOUSING-ABS			
			LENS-PC			
			BRACKET-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V ~ 24V	0.08W	MAX. 0.255A	
			AC110V ~ 220V		MAX. 0.067A	
VOLUME			MAX. 80dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP65			
CABLE ENTRY			ø13.5 LEAD HOLE			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS	0.5~3	f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	3~6	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	6~30	±0.1	±0.2	±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	30~120	±0.15	±0.3	±0.5	±1	TITLE			MODEL			
	120~400	±0.2	±0.5	±0.8	±1.5	Q100LP			Q100LP			
	400~1000	±0.3	±0.8	±1.2	±2.5	OUTLINE DRAWING			Q100LP			
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.			
	10~50	±0°30'		±1°	±2°				Q100LP_OUT			
	50~120	±0°20'		±0°30'	±1°				SCALE	SIZE	REV	SHEET
	120~400	±0°10'		±0°13'	±0°30'				N/S	A4	00	1/1