



※ *(380) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SED			
MATERIAL			HOUSING-AL			
			LENS-PC			
			REFLECTOR-HEAT RESISTING ABS			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	15W	MAX. 3.755A	
			DC24V		MAX. 1.788A	
			AC110V		MAX. 0.422A	
			AC220V		MAX. 0.211A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-						
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE						
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE						
	3~6			±0.3	±0.5		S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30						
	6~30	±0.1	±0.2	±0.5	±1		TITLE SED OUTLINE DRAWING											
	30~120	±0.15	±0.3	±0.8	±1.5								MODEL SED					
	120~400	±0.2	±0.5	±1.2	±2.5													
400~1000	±0.3	±0.8	±2	±4	DWG. NO. SED_OUT													
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°													
	10~50	±0°30'		±1°	±2°							SCALE N/S SIZE A4 REV 00 SHEET 1/1						
	50~120	±0°20'		±0°30'	±1°													
	120~400	±0°10'		±0°13'	±0°30'													