



MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO	S125SOLEH-AU
MATERIAL	HOUSING-ABS
	LENS-PC
FLASHES PER MIN.	40 ~ 80
LED CURRENT	MAX. 0.820A
BATTERY VOLTAGE	3.7V
BATTERY CURRENT	2.6AH
OPERATING HOUR	12Hr
PROTECTION GRADE	WATER & DUST PROOF IP55
COLOR OF HOUSING	MAKER STANDARD
ACTION	SOLAR CELL LED FLASHING LIGHT

SLIDE	L
MIN.	440
MAX.	780

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-								
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE			
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2017.02.09				
	3~6			±0.3	±0.5										
	6~30	±0.1	±0.2	±0.5	±1										
	30~120	±0.15	±0.3	±0.8	±1.5										
	120~400	±0.2	±0.5	±1.2	±2.5										
400~1000	±0.3	±0.8	±2	±4	TITLE S125SOLEH-AU OUTLINE DRAWING				MODEL S125SOLEH-AU						
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°					DWG. NO. S125SOLEH-AU_OUT					
	10~50	±0°30'		±1°	±2° <th colspan="3">SCALE N/S</th> <th>SIZE A4</th> <th>REV 00</th> <th>SHEET 1/1</th>					SCALE N/S			SIZE A4	REV 00	SHEET 1/1
	50~120	±0°20'		±0°30'	±1°										
	120~400	±0°10'		±0°13'	±0°30'										

Qlight

A4(297X210)