



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO		PSDF-SHD			
MATERIAL		HOUSING-AL			
		LENS-PC			
		REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS		RED			
FLASHING PER MIN.		60 ~ 80			
USE VOLT.	LED	CURRENT	AC220V	0.08W	MAX. 0.143A
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		1/2" PF			
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2			
ACTION		LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY			APRV BY	VIEW	DATE
	3~6			±0.3	±0.5		J.H.PARK	J.H.PARK		J.K.HAN	3	2019.06.19
	6~30	±0.1	±0.2	±0.5	±1		TITLE			MODEL		
	30~120	±0.15	±0.3	±0.8	±1.5		PSDF-SHD			PSDF-SHD		
	120~400	±0.2	±0.5	±1.2	±2.5		OUTLINE DRAWING					
FOR ANGULAR DIMENSIONS	0~10			±2	±4					PSDF-SHD_OUT		
	10~50	±1°	±1°30'	±1°	±3°					DWG. NO.		
	50~120	±0°30'	±1°	±2°								
	120~400	±0°20'	±0°30'	±1°								
	120~400	±0°10'	±0°13'	±0°30'						SCALE	SIZE	REV
										N/S	A4	00
												SHEET
												1/1