



FITTING HOLES
(SCALE 6:1)

※ POWER CABLE : DC TYPE - UL2464 AWG22(0.3sq X 2C) 400mm
AC TYPE - VCTFK (0.75sq) x 2C 400mm

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		PSQEL			
MATERIAL		SIDE COVER : ABS			
		LENS-PC			
		BRACKET-SUS201			
COLOR OF LENS		UNCLEAR			
MODEL		PSQEL-200	PSQEL-300	PSQEL-400	PSQEL-500
CURRENT	DC24V	MAX. 0.145A	MAX. 0.215A	MAX. 0.285A	MAX. 0.358A
	AC110V	MAX. 0.196A	MAX. 0.202A	MAX. 0.206A	MAX. 0.216A
	AC220V	MAX. 0.095A	MAX. 0.098A	MAX. 0.100A	MAX. 0.105A
LED		CHIP LED			
PROTECTION GRADE		NON WATER-PROOF			

MODEL	A	B	C
PSQEL-200	220	200	16~170
PSQEL-300	320	300	16~270
PSQEL-400	420	400	16~370
PSQEL-500	520	500	16~470

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3
	6~30	±0.1	±0.2	±0.5	±1							DATE
	30~120	±0.15	±0.3	±0.8	±1.5							2016.08.30
	120~400	±0.2	±0.5	±1.2	±2.5							
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			TITLE		MODEL		
	0~10	±1°		±1°30'	±3°			PSQEL		PSQEL		
	10~50	±0°30'		±1°	±2°			OUTLINE DRAWING		PSQEL		
	50~120	±0°20'		±0°30'	±1°			Qlight		DWG. NO.		
	120~400	±0°10'		±0°13'	±0°30'					PSQEL		
								SCALE	SIZE	REV	SHEET	
								N/S	A4	00	1/1	

A4(297X210)