



| MARK | DATE | REVISION | REVISER | APP .BY |
|------|------|----------|---------|---------|
| △ | | | | |
| △ | | | | |
| △ | | | | |

| | | | | | |
|------------------|-----|-------------------------|-----------|----------|----------|
| MODEL NO | | QL9840-7 | | | |
| MATERIAL | | BODY-AL | | | |
| | | LENS-PC | | | |
| | | BRACKET-SUS | | | |
| COLOR OF LENS | | TRANSLUCENT | | | |
| USE VOLT. | LED | CURRENT | DC12V~24V | CHIP LED | MAX.1.0A |
| PROTECTION GRADE | | WATER & DUST PROOF IP67 | | | |
| CABLE ENTRY | | φ7 | | | |

| ISO2768-1 : CLASS OF TOLERANCE | | | | | | SURFACE FINISH | - | - | - | - | 1 | - |
|--------------------------------|---------|--------|------|--------|--------|--------------------------------------|---|--|--------------------------|--------------|--------------------|-----------|
| FOR LINEAR DIMENSIONS | | f | m | ⌀ | v | | Nr. | DWG. NO. | TITLE/ NAME | MAT'L | QTY | REFERENCE |
| | 0.5~3 | ±0.05 | ±0.1 | ±0.2 | - | DSND BY J.H.PARK | CHKD BY J.H.PARK | CHKD BY  | APRV BY J.K.HAN | VIEW 3 | DATE 2019.07.30 | |
| | 3~6 | | | ±0.3 | ±0.5 | | | | | | | |
| | 6~30 | ±0.1 | ±0.2 | ±0.5 | ±1 | TITLE QL9840-7 OUTLINE DRAWING |  | MODEL QL9840-7 | | | | |
| | 30~120 | ±0.15 | ±0.3 | ±0.8 | ±1.5 | | | | DWG. NO. QL9840-7_OUT | | | |
| | 120~400 | ±0.2 | ±0.5 | ±1.2 | ±2.5 | | | | | SCALE N/S | SIZE A4 | REV 00 |
| 400~1000 | ±0.3 | ±0.8 | ±2 | ±4 | | | | | | | | |
| FOR ANGULAR DIMENSIONS | 0~10 | ±1° | | ±1°30' | ±3° | | | | | | | |
| | 10~50 | ±0°30' | | ±1° | ±2° | | | | | | | |
| | 50~120 | ±0°20' | | ±0°30' | ±1° | | | | | | | |
| | 120~400 | ±0°10' | | ±0°13' | ±0°30' | | | | | | | |