



※ *(167) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	SH1TLR			
MATERIAL	HOUSING-AL			
	LENS-PC			
	REFLECTOR-PC			
	PROTECTION CAGE-SUS316L			
COLOR OF LENS	RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.	120 ~ 140			
USE VOLT.	LED	CURRENT	1W	MAX. 0.422A
				MAX. 0.266A
				MAX. 0.082A
				MAX. 0.041A
PROTECTION GRADE	WATER & DUST PROOF IP66			
CABLE ENTRY	1/2" PF			
COLOR OF HOUSING	MUNSELL NO. 7.5BG 7/2			
ACTION	LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS		f	m	(C)		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5-3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3-6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6-30	±0.1	±0.2	±0.5	±1	TITLE SH1TLR OUTLINE DRAWING					
	30-120	±0.15	±0.3	±0.8	±1.5	MODEL SH1TLR					
	120-400	±0.2	±0.5	±1.2	±2.5	DWG. NO. SH1TLR_OUT					
400-1000	±0.3	±0.8	±2	±4	SCALE N/S						
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°	SIZE A4					
	10-50	±0°30'		±1°	±2°	REV 00					
	50-120	±0°20'		±0°30'	±1°	SHEET 1/1					
	120-400	±0°10'		±0°13'	±0°30'	A4(297X210)					

