



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	SW2TS-RL
MATERIAL	HEAD & BODY - SUS316L BOLT, NUT & ETC.-SUS304
CONTACT	2CKT-DB, 1A1B, 250VAC 6A
PROTECTION GRADE	WATER & DUST PROOF-IP66
CABLE ENTRY	PF1/2"
COLOR	MAKER STANDARD
INSULATION RESISTANCE	100MΩ MIN. AT 500V DC

Operating Characteristics

OF max.g	1,380
RF min.g	260
PT	25° ± 5°
MD max.	10°
TT min	70°

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v	
FOR LINEAR DIMENSIONS	0.5-3			±0.2	-
	3-6	±0.05	±0.1	±0.3	±0.5
	6-30	±0.1	±0.2	±0.5	±1
	30-120	±0.15	±0.3	±0.8	±1.5
	120-400	±0.2	±0.5	±1.2	±2.5
	400-1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0-10		±1°	±1°30'	±3°
	10-50		±0°30'	±1°	±2°
	50-120		±0°20'	±0°30'	±1°
	120-400		±0°10'	±0°13'	±0°30'

-		-		-		-	
Nr.	DWG. NO.	TITLE/NAME		MAT'L	QTY	REFERENCE	
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE		
J.I.BAE	Y.H.JOO		J.K.HAN	3	2025.06.29		
TITLE				MODEL			
SW2TS-RL OUTLINE DRAWING				SW2TS-RL			
DWG. NO.				SCALE			
SW2TS-RL-OUT				N/S			
SIZE	REV	SHEET					
A4	00	1/1					

