



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO	S80SM				
MATERIAL	HOUSING-ABS				
	LENS-AS				
COLOR OF LENS	RED(), AMBER(), GREEN(), BLUE()				
FLASHES PER MIN.	60 ~ 80				
USE VOLT.	XENON	CURRENT	DC12V ~ DC24V	4W	MAX. 0.435A
PROTECTION GRADE	WATER & DUST PROOF IP54				
CABLE ENTRY	ø10 LEAD HOLE				
COLOR OF HOUSING	MAKER STANDARD				
ACTION	XENON LAMP STROBE LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2019.03.20
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO.			
	10~50	±0°30'		±1°	±2°				S80SM_OUT			
	50~120	±0°20'		±0°30'	±1°				SCALE			
	120~400	±0°10'		±0°13'	±0°30'				N/S			
									A4			
								REV	SHEET			
								00	1/1			

A4(297X210)