




MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO			MGA50-R-12 / MGA50-R-24		
MATERIAL			PC		
COLOR OF LENS			RED		
FLASHES. PER MIN			60 ~ 80		
USE VOLT.	LED	CURRNET	DC12V	1.2W	0.085A
			DC24V		0.050A
PROTECTION GRADE			WATER & DUST PROOF IP65		
ACTION			LED STEADY / FLASHING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	-	-		
FOR LINEAR DIMENSIONS		f	(m)	c	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE		
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY H.M.SEO	CHKD BY Y.H.JOO	CHKD BY 	APRV BY J.W.KIM	VIEW 3	DATE 2022.06.14		
	3~6			±0.3	±0.5									
	6~30	±0.1	±0.2	±0.5	±1	TITLE MGA50-R OUTLINE DRAWING			MODEL MTG50 SERIES					
	30~120	±0.15	±0.3	±0.8	±1.5									
	120~400	±0.2	±0.5	±1.2	±2.5									
400~1000	±0.3	±0.8	±2	±4										
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				DWG. NO. MGA50-R_OUT					
	10~50	±0°30'		±1°	±2°				SCALE N/S			SIZE A4	REV 00	SHEET 1/1
	50~120	±0°20'		±0°30'	±1°									
	120~400	±0°10'		±0°13'	±0°30'									