



※ *(198) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			SH2S			
MATERIAL			HOUSING-AL			
			LENS-PC			
			PROTECTION CAGE-SUS316L			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.			60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	6W	MAX. 1.001A	
			DC24V		MAX. 0.616A	
			AC110V		MAX. 0.133A	
			AC220V		MAX. 0.106A	
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2" PF			
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2			
ACTION			XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1			TITLE SH2S OUTLINE DRAWING					
	30~120	±0.15	±0.3	±0.8	±1.5			MODEL SH2S					
	120~400	±0.2	±0.5	±1.2	±2.5			DWG. NO. SH2S_OUT					
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4			SCALE N/S					
	0~10	±1°		±1°30'	±3°			SIZE A4					
	10~50	±0°30'		±1°	±2°			REV 00					
	50~120	±0°20'		±0°30'	±1°			SHEET 1/1					
	120~400	±0°10'		±0°13'	±0°30'								

Qlight

A4(297X210)