



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO			SEBAS		
			HOUSING-AL		
MATERIAL			LENS-TEMPERED GLASS		
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()		
FLASHING PER MIN.			60 ~ 80		
USE VOLT.	XENON	CURRENT	DC24V	6W	MAX. 0.666A
			AC110V		MAX. 0.222A
			AC220V		MAX. 0.150A
PROTECTION GRADE			WATER & DUST PROOF IP55		
CABLE ENTRY			1/2" NPT		
COLOR OF HOUSING			MUNSELL NO. 7.5BG 7/2		
ACTION			XENON LAMP STROBE LIGHT		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2020.08.31	
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°				MODEL SEBAS			
	10~50	±0°30'		±1°	±2°				DWG. NO. SEBAS_OUT			
	50~120	±0°20'		±0°30'	±1°				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	120~400	±0°10'		±0°13'	±0°30'							